



Bükme 45° 300mm her iki tarafta  
uzatılmış enjeksiyon kalıplı + kaynaklı  
Alın + E-füzyon kaynağı PP gri

| Boyut | Kod            | Detay                      | Ağırlık | da(OD)<br>mm | s mm | L mm | L1<br>mm | L2<br>mm |
|-------|----------------|----------------------------|---------|--------------|------|------|----------|----------|
| 110   | 11.001.2110.33 | 110X3,4 SDR33<br>ISO S-16  | 0.800   | 110          | 3,4  | 300  | 356      | 346      |
| 125   | 11.001.2125.33 | 125X3,9 SDR33<br>ISO S-16  | 1.085   | 125          | 3,9  | 300  | 362      | 352      |
| 140   | 11.001.2140.33 | 140X4,3 SDR33<br>ISO S-16  | 1.400   | 140          | 4,3  | 300  | 368      | 358      |
| 160   | 11.001.2160.33 | 160X4,9 SDR33<br>ISO S-16  | 1.760   | 160          | 4,9  | 300  | 389      | 364      |
| 180   | 11.001.2180.33 | 180X5,5 SDR33<br>ISO S-16  | 2.240   | 180          | 5,5  | 300  | 395      | 375      |
| 200   | 11.001.2200.33 | 200X6,2 SDR33<br>ISO S-16  | 3.000   | 200          | 6,2  | 300  | 403      | 383      |
| 225   | 11.001.2225.33 | 225X6,9 SDR33<br>ISO S-16  | 3.630   | 225          | 6,9  | 300  | 403      | 383      |
| 250   | 11.001.2250.33 | 250X7,7 SDR33<br>ISO S-16  | 5.000   | 250          | 7,7  | 300  | 413      | 393      |
| 280   | 11.001.2280.33 | 280X8,6 SDR33<br>ISO S-16  | 6.050   | 280          | 8,6  | 300  | 438      | 408      |
| 315   | 11.001.2315.33 | 315X9,7 SDR33<br>ISO S-16  | 8.300   | 315          | 9,7  | 300  | 464      | 424      |
| 355   | 11.001.2355.33 | 355X10,9 SDR33<br>ISO S-16 | 10.400  | 355          | 10,9 | 300  | 464      | 424      |



| Boyut | Kod            | Detay                         | Ağırlık | da(OD)<br>mm | s mm | L mm | L1<br>mm | L2<br>mm |
|-------|----------------|-------------------------------|---------|--------------|------|------|----------|----------|
| 400   | 11.001.2400.33 | 400X12,3 SDR33<br>ISO S-16    | 12.750  | 400          | 12,3 | 300  | 469      | 424      |
| 450   | 11.001.2450.33 | 450X13,8 SDR33<br>ISO S-16    | 18.100  | 450          | 13,8 | 300  | 511      | 466      |
| 355   | 11.001.2355.17 | 355X20,1 SDR17,6<br>ISO S-8,3 | 18.900  | 355          | 20,1 | 300  | 464      | 424      |
| 400   | 11.001.2400.17 | 400X22,7 SDR17,6<br>ISO S-8,3 | 22.700  | 400          | 22,7 | 300  | 464      | 424      |
| 450   | 11.001.2450.17 | 450X25,5 SDR17,6<br>ISO S-8,3 | 32.600  | 450          | 25,5 | 300  | 511      | 466      |
| 500   | 11.001.2500.17 | 500X28,3 SDR17,6<br>ISO S-8,3 | 39.200  | 500          | 28,3 | 300  | 511      | 466      |
| 355   | 11.001.2355.11 | 355X32,2 SDR11<br>ISO S-5     | 28.900  | 355          | 32,2 | 300  | 464      | 424      |
| 400   | 11.001.2400.11 | 400X36,3 SDR11<br>ISO S-5     | 34.700  | 400          | 36,3 | 300  | 469      | 424      |
| 450   | 11.001.2450.11 | 450X40,9 SDR11<br>ISO S-5     | 47.800  | 450          | 40,9 | 300  | 511      | 466      |
| 500   | 11.001.2500.11 | 500X45,4 SDR11<br>ISO S-5     | 59.300  | 500          | 45,4 | 300  | 511      | 466      |