



T 45° uzun spigot enjeksiyon kalıplı Alın +
E-füzyon kaynağı PPR gri

Boyut	Kod	Detay	Ağırlık	da(OD) mm	s mm	z mm	L mm	L1 mm	L3 mm
63	11.036.0063.17	63X3,8 SDR17 ISO S-8	0.390	63	3,8	170	262	93	64
75	11.036.0075.17	75X4,5 SDR17 ISO S-8	0.598	75	4,5	192	300	103	71
90	11.036.0090.17	90X5,4 SDR17 ISO S-8	1.010	90	5,4	230	351	122	80
110	11.036.0110.17	110X6,6 SDR17 ISO S-8	1.540	110	6,6	250,5	385	131	84
125	11.036.0125.17	125X7,4 SDR17 ISO S-8	2.350	125	7,4	292,5	431	140	89
140	11.036.0140.17	140X8,3 SDR17 ISO S-8	3.260	140	8,3	315,5	468	150	94
160	11.036.0160.17	160X9,5 SDR17 ISO S-8	4.680	160	9,5	369	530	166	100
180	11.036.0180.17	180X10,7 SDR17 ISO S-8	6.260	180	10,7	390	568	179	107
200	11.036.0200.17	200X11,9 SDR17 ISO S-8	8.320	200	11,9	416	609	191	114
225	11.036.0225.17	225X13,4 SDR17 ISO S-8	11.900	225	13,4	474	678	206	122
32	11.036.0032.11	32X2,9 SDR11 ISO S-5	0.110	32	2,9	131	195	65	45



Boyut	Kod	Detay	Ağırlık	da(OD) mm	s mm	z mm	L mm	L1 mm	L3 mm
40	11.036.0040.11	40X3,7 SDR11 ISO S-5	0.170	40	3,7	137	211	72	50
50	11.036.0050.11	50X4,6 SDR11 ISO S-5	0.270	50	4,6	148,5	228	81	56
63	11.036.0063.11	63X5,8 SDR11 ISO S-5	0.496	63	5,8	170	262	93	64
75	11.036.0075.11	75X6,8 SDR11 ISO S-5	0.786	75	6,8	192	300	103	71
90	11.036.0090.11	90X8,2 SDR11 ISO S-5	1.295	90	8,2	230	351	122	83
110	11.036.0110.11	110X10,0 SDR11 ISO S-5	2.045	110	10	250,5	385	131	84
125	11.036.0125.11	125X11,4 SDR11 ISO S-5	3.000	125	11,4	300	431	140	90
140	11.036.0140.11	140X12,7 SDR11 ISO S-5	4.100	140	12,7	323	467	150	94
160	11.036.0160.11	160X14,6 SDR11 ISO S-5	6.196	160	14,6	362	526	166	100
180	11.036.0180.11	180X16,4 SDR11 ISO S-5	8.380	180	16,4	385	568	179	107
200	11.036.0200.11	200X18,2 SDR11 ISO S-5	10.850	200	18,2	422,5	609	191	114
225	11.036.0225.11	225X20,5 SDR11 ISO S-5	15.420	225	20,5	474	678	206	122