



Saplama Flanş DIN uzun spigot  
enjeksiyon kalıplı Alın + E-füzyon kaynağı  
PPR gri

Boyut	Kod	Detay	Ağırlık	da(OD) mm	s mm	L mm	L3 mm	d3 mm	d4 mm	h mm
20	11.062.0020.11	20X1,9 SDR11 ISO S-5	0.020	20	1,9	88	64	27	45	7
25	11.062.0025.11	25X2,3 SDR11 ISO S-5	0.035	25	2,3	88	64	33	58	9
32	11.062.0032.11	32X2,9 SDR11 ISO S-5	0.054	32	2,9	89	61	40	68	10
40	11.062.0040.11	40X3,7 SDR11 ISO S-5	0.083	40	3,7	102	67	50	78	11
50	11.062.0050.11	50X4,6 SDR11 ISO S-5	0.110	50	4,6	102	69	61	88	12
63	11.062.0063.11	63X5,8 SDR11 ISO S-5	0.210	63	5,8	124	78	75	102	14
75	11.062.0075.11	75X6,8 SDR11 ISO S-5	0.295	75	6,8	127,5	89	89	122	16
90	11.062.0090.11	90X8,2 SDR11 ISO S-5	0.438	90	8,2	143	104	105	138	17



Boyut	Kod	Detay	Ağırlık	da(OD) mm	s mm	L mm	L3 mm	d3 mm	d4 mm	h mm
110	11.062.0110.11	110X10,0 SDR11 ISO S-5	0.692	110	10	162	115	125	158	18
125	11.062.0125.11	125X11,4 SDR11 ISO S-5	0.841	125	11,4	173	124	132	158	25
140	11.062.0140.11	140X12,7 SDR11 ISO S-5	1.240	140	12,7	193	133	155	188	25
160	11.062.0160.11	160X14,6 SDR11 ISO S-5	1.680	160	14,6	203	148	175	212	25
180	11.062.0180.11	180X16,4 SDR11 ISO S-5	1.940	180	16,4	213	158	183	212	30
200	11.062.0200.11	200X18,2 SDR11 ISO S-5	3.110	200	18,2	213	140	232	268	32
225	11.062.0225.11	225X20,5 SDR11 ISO S-5	3.180	225	20,5	213	145	235	268	32
250	11.062.0250.11	250X22,7 SDR11 ISO S-5	4.500	250	22,7	210	132	285	320	35
280	11.062.0280.11	280X25,4 SDR11 ISO S-5	4.860	280	25,4	220	143	288	320	35
315	11.062.0315.11	315X28,6 SDR11 ISO S-5	7.000	315	28,6	238	154	335	370	35