



MULTI-Bend 90° uzun spigot enjeksiyon kalıplı Alın + E-füzyon kaynağı PPR gri

Boyut	Kod	Detay	Ağırlık	da(OD) mm	s mm	r mm	z mm	L3 mm
63	11.068.0063.17	63X3,8 SDR17 ISO S-8	0.181	63	3,8	63	129,5	66,5
75	11.068.0075.17	75X4,5 SDR17 ISO S-8	0.290	75	4,5	75	150	75
90	11.068.0090.17	90X5,4 SDR17 ISO S-8	0.473	90	5,4	90	168	76
110	11.068.0110.17	110X6,6 SDR17 ISO S-8	0.788	110	6,6	110	192	82
125	11.068.0125.17	125X7,4 SDR17 ISO S-8	1.170	125	7,4	125	218	92
140	11.068.0140.17	140X8,3 SDR17 ISO S-8	1.580	140	8,3	140	241	100
160	11.068.0160.17	160X9,5 SDR17 ISO S-8	2.231	160	9,5	160	261,5	100,5
180	11.068.0180.17	180X10,7 SDR17 ISO S-8	3.080	180	10,7	180	290,5	109
200	11.068.0200.17	200X11,9 SDR17 ISO S-8	4.030	200	11,9	200	318,5	118,5
225	11.068.0225.17	225X13,4 SDR17 ISO S-8	5.810	225	13,4	225	353	125
250	11.068.0250.17	250X14,8 SDR17 ISO S-8	7.040	250	14,8	250	389	135



Boyut	Kod	Detay	Ağırlık	da(OD) mm	s mm	r mm	z mm	L3 mm
280	11.068.0280.17	280X16,6 SDR17 ISO S-8	9.800	280	16,6	280	429	146
315	11.068.0315.17	315X18,7 SDR17 ISO S-8	14.000	315	18,7	315	475	158
20	11.068.0020.11	20X1,9 SDR11 ISO S-5	0.014	20	1,9	20	60	40
25	11.068.0025.11	25X2,3 SDR11 ISO S-5	0.023	25	2,3	25	68,5	42,5
32	11.068.0032.11	32X2,9 SDR11 ISO S-5	0.041	32	2,9	32	79	47
40	11.068.0040.11	40X3,7 SDR11 ISO S-5	0.073	40	3,7	40	92,5	52
50	11.068.0050.11	50X4,6 SDR11 ISO S-5	0.131	50	4,6	50	108,5	58,5
63	11.068.0063.11	63X5,8 SDR11 ISO S-5	0.252	63	5,8	63	129,5	66,5
75	11.068.0075.11	75X6,8 SDR11 ISO S-5	0.403	75	6,8	75	150	75
90	11.068.0090.11	90X8,2 SDR11 ISO S-5	0.659	90	8,2	90	168	76
110	11.068.0110.11	110X10,0 SDR11 ISO S-5	1.107	110	10	110	192	82
125	11.068.0125.11	125X11,4 SDR11 ISO S-5	1.639	125	11,4	125	218	92
140	11.068.0140.11	140X12,7 SDR11 ISO S-5	2.240	140	12,7	140	241	100
160	11.068.0160.11	160X14,6 SDR11 ISO S-5	3.160	160	14,6	160	261,5	100,5
180	11.068.0180.11	180X16,4 SDR11 ISO S-5	4.330	180	16,4	180	290,5	109
200	11.068.0200.11	200X18,2 SDR11 ISO S-5	5.800	200	18,2	200	318,5	118,5
225	11.068.0225.11	225X20,5 SDR11 ISO S-5	8.150	225	20,5	225	353	125



Boyut	Kod	Detay	Ağırlık	da(OD) mm	s mm	r mm	z mm	L3 mm
250	11.068.0250.11	250X22,7 SDR11 ISO S-5	10.400	250	22,7	250	389	135
280	11.068.0280.11	280X25,4 SDR11 ISO S-5	14.220	280	25,4	280	429	146
315	11.068.0315.11	315X28,6 SDR11 ISO S-5	19.820	315	28,6	315	475	158