



90° bükülmüş kısa musluk alev geciktirici enjeksiyon kalıplı Alın kaynaklı PP'ler gri

Boyut	Kod	Detay	Ağırlık	da(OD) mm	s mm	r mm	z mm
110	17.001.0110.33	110X3,4 SDR33 ISO S-16	0.253	110	3,4	110	120
160	17.001.0160.33	160X4,9 SDR33 ISO S-16	0.790	160	4,9	155	180
180	17.001.0180.33	180X5,5 SDR33 ISO S-16	1.002	180	5,5	180	200
200	17.001.0200.33	200X6,2 SDR33 ISO S-16	1.420	200	6,2	200	220
225	17.001.0225.33	225X6,9 SDR33 ISO S-16	1.920	225	6,9	225	245
250	17.001.0250.33	250X7,7 SDR33 ISO S-16	2.940	250	7,7	265	290
280	17.001.0280.33	280X8,6 SDR33 ISO S-16	3.650	280	8,6	260	290
315	17.001.0315.33	315X9,7 SDR33 ISO S-16	5.200	315	9,7	300	340
355	17.001.0355.33	355X10,9 SDR33 ISO S-16	6.680	355	10,9	300	340
400	17.001.0400.33	400X12,3 SDR33 ISO S-16	8.280	400	12,3	300	345
20	17.001.0020.11	20X1,9 SDR11 ISO S-5	0.008	20	1,9	23	32
25	17.001.0025.11	25X2,3 SDR11 ISO S-5	0.012	25	2,3	30	35
32	17.001.0032.11	32X2,9 SDR11 ISO S-5	0.020	32	2,9	32	43
40	17.001.0040.11	40X3,7 SDR11 ISO S-5	0.033	40	3,7	40	50
50	17.001.0050.11	50X4,6 SDR11 ISO S-5	0.065	50	4,6	50	60
63	17.001.0063.11	63X5,8 SDR11 ISO S-5	0.117	63	5,8	63	70
75	17.001.0075.11	75X6,8 SDR11 ISO S-5	0.202	75	6,8	75	85
90	17.001.0090.11	90X8,2 SDR11 ISO S-5	0.360	90	8,2	90	100



Boyut	Kod	Detay	Ağırlık	da(OD) mm	s mm	r mm	z mm
110	17.001.0110.11	110X10,0 SDR11 ISO S-5	0.580	110	10	110	124
140	17.001.0140.11	140X12,7 SDR11 ISO S-5	1.220	140	12,7	140	150
160	17.001.0160.11	160X14,6 SDR11 ISO S-5	1.920	160	14,6	155	180