



90° bükümlü kısa musluk enjeksiyon kalıplı Alın + IR kaynaklı PVDF doğal

Boyut	Kod	Detay	Ağırlık	da(OD) mm	s mm	r mm	z mm
180	30.001.0180.33	180X5,5 SDR33 ISO S-16	1.915	180	5,5	175	200
200	30.001.0200.33	200X6,2 SDR33 ISO S-16	2.756	200	6,2	196	217
250	30.001.0250.33	250X7,7 SDR33 ISO S-16	5.460	250	7,7	250	287
280	30.001.0280.33	280X8,6 SDR33 ISO S-16	6.911	280	8,6	280	288
315	30.001.0315.33	315X9,7 SDR33 ISO S-16	10.108	315	9,7	300	338
125	30.001.0125.21	125X6,0 SDR21 ISO S-10	0.944	125	6	125	135
180	30.001.0180.21	180X8,6 SDR21 ISO S-10	2.870	180	8,6	175	200
200	30.001.0200.21	200X9,6 SDR21 ISO S-10	3.775	200	9,6	196	217
250	30.001.0250.21	250X11,9 SDR21 ISO S-10	7.945	250	11,9	250	287
280	30.001.0280.21	280X13,4 SDR21 ISO S-10	10.290	280	13,4	280	288