



Körtapa kısa spigot işlenmiş Uç + IR  
kaynaklı PVDF doğal

Boyut	Kod	Detay	Ağırlık	da(OD) mm	s mm	s1 mm	L mm
125	30.302.0125.33	125X3,9 SDR33 ISO S-16	0.507	125	3,9	20	35
140	30.302.0140.33	140X4,3 SDR33 ISO S-16	0.623	140	4,3	20	35
160	30.302.0160.33	160X4,9 SDR33 ISO S-16	0.800	160	4,9	20	35
200	30.302.0200.33	200X6,2 SDR33 ISO S-16	1.265	200	6,2	20	35
225	30.302.0225.33	225X6,9 SDR33 ISO S-16	1.533	225	6,9	20	35
125	30.302.0125.21	125X6,0 SDR21 ISO S-10	0.540	125	6	20	35
140	30.302.0140.21	140X6,7 SDR21 ISO S-10	0.800	140	6,7	20	35
160	30.302.0160.21	160X7,7 SDR21 ISO S-10	0.849	160	7,7	20	35
200	30.302.0200.21	200X9,6 SDR21 ISO S-10	1.312	200	9,6	20	35
225	30.302.0225.21	225X10,8 SDR21 ISO S-10	1.460	225	10,8	20	35