



Reducer concentric machined Butt + IR-welding PVDF natural

Boyut	Kod	Detay	Ağırlık	da(OD) mm	da1(OD1) mm	s mm	s1 mm	L mm	L1 mm	L2 mm
140/125	30.317.1412.33	140/125 SDR33 ISO S-16	0.392	140	125	4,3	3,9	100	25	30
200/160	30.317.2016.33	200/160 SDR33 ISO S-16	0.847	200	160	6,2	4,9	120	26	30
63/20	30.317.6320.21	63/20 SDR21 ISO S-10	0.060	63	20	3	1,9	80	25	20
90/20	30.317.9020.21	90/20 SDR21 ISO S-10	0.145	90	20	4,3	1,9	80	33	20
90/32	30.317.9032.21	90/32 SDR21 ISO S-10	0.200	90	32	4,3	2,4	80	33	20
90/50	30.317.9050.21	90/50 SDR21 ISO S-10	0.120	90	50	4,3	3	80	33	20
110/50	30.317.1150.21	110/50 SDR21 ISO S-10	0.210	110	50	5,3	3	100	33	20
110/75	30.317.1175.21	110/75 SDR21 ISO S-10	0.298	110	75	5,3	3,6	100	33	20



Boyut	Kod	Detay	Ağırlık	da(OD) mm	da1(OD1) mm	s mm	s1 mm	L mm	L1 mm	L2 mm
125/63	30.317.1263.21	125/63 SDR21 ISO S-10	0.405	125	63	6	3	100	25	20
125/90	30.317.1290.21	125/90 SDR21 ISO S-10	0.390	125	90	6	4,3	100	25	20
125/110	30.317.1211.21	125/110 SDR21 ISO S-10	0.467	125	110	6	5,3	100	25	30
140/90	30.317.1490.21	140/90 SDR21 ISO S-10	0.483	140	90	6,7	4,3	100	25	20
140/125	30.317.1412.21	140/125 SDR21 ISO S-10	0.450	140	125	6,7	6	100	25	30
180/90	30.317.1890.21	180/90 SDR21 ISO S-10	0.918	180	90	8,6	4,3	130	30	20
200/160	30.317.2016.21	200/160 SDR21 ISO S-10	1.245	200	160	9,6	7,7	120	26	30