



Yüksek basınç flanşı DIN PN25
sızdırmazlık halkası + destek halkası dahil
ve merkezleme halkası delikli PN25 Alttan
kaynaklı PE 100-RC siyah

Boyut	Kod	Detay	Ağırlık	da(OD) mm	s mm	L mm	L3 mm	d mm	d2 mm	d4 mm	h mm
63	70.292.0063.07	63X8,6 SDR7,4 ISO S-3,2	2.830	63	8,6	100	63	165	18	102	17
75	70.292.0075.07	75X10,3 SDR7,4 ISO S-3,2	3.810	75	10,3	105	63	185	18	122	20
90	70.292.0090.07	90X12,3 SDR7,4 ISO S-3,2	4.994	90	12,3	105	60	200	18	137	21
110	70.292.0110.07	110X15,1 SDR7,4 ISO S-3,2	7.000	110	15,1	110	62	235	22	163	22
125	70.292.0125.07	125X17,1 SDR7,4 ISO S-3,2	6.580	125	17,1	120	64	235	22	163	30
140	70.292.0140.07	140X19,2 SDR7,4 ISO S-3,2	9.470	140	19,2	120	62	270	26	189	30
160	70.292.0160.07	160X21,9 SDR7,4 ISO S-3,2	12.600	160	21,9	120	60	300	26	219	30
180	70.292.0180.07	180X24,6 SDR7,4 ISO S-3,2	13.800	180	24,6	120	60	300	26	219	30



Boyut	Kod	Detay	Ağırlık	da(OD) mm	s mm	L mm	L3 mm	d mm	d2 mm	d4 mm	h mm
200	70.292.0200.07	200X27,4 SDR7,4 ISO S-3,2	19.400	200	27,4	135	64	360	26	279	39
225	70.292.0225.07	225X30,8 SDR7,4 ISO S-3,2	17.700	225	30,8	135	64	360	26	279	39
250	70.292.0250.07	250X34,8 SDR7,4 ISO S-3,2	28.400	250	34,8	145	60	425	30	335	50
280	70.292.0280.07	280X38,3 SDR7,4 ISO S-3,2	25.000	280	38,3	145	60	425	30	335	50
315	70.292.0315.07	315X43,1 SDR7,4 ISO S-3,2	41.000	315	43,1	195	100	485	30	395	57
355	70.292.0355.07	355X48,5 SDR7,4 ISO S-3,2	57.000	355	48,5	205	100	555	33	452	63
400	70.292.0400.07	400X54,7 SDR7,4 ISO S-3,2	170.000	400	54,7	220	102	620	36	509	70
450	70.292.0450.07	450X61,5 SDR7,4 ISO S-3,2	161.000	450	61,5	245	104	730	36	619	83
500	70.292.0500.07	500X68,3 SDR7,4 ISO S-3,2	121.000	500	68,3	245	101	730	36	619	86
560	70.292.0560.07	560X76,5 SDR7,4 ISO S-3,2	268.000	560	76,5	260	102	845	39	726	90