



45° Bükme parçalı değer düşürme faktörü
0,8 Altın kaynak PE 100-RC siyah

Boyut	Kod	Detay	Ağırlık	da(OD) mm	s mm	r mm	z mm
560	70.330.0560.41	560X13,7 SDR41 ISO S-20	27.890	560	13,7	840	587
630	70.330.0630.41	630X15,4 SDR41 ISO S-20	36.000	630	15,4	945	616
710	70.330.0710.41	710X17,4 SDR41 ISO S-20	52.000	710	17,4	1.065	700
800	70.330.0800.41	800X19,6 SDR41 ISO S-20	70.000	800	19,6	1.200	738
900	70.330.0900.41	900X22,0 SDR41 ISO S-20	93.000	900	22	1.330	780
1000	70.330.1000.41	1000X24,5 SDR41 ISO S-20	136.000	1.000	24,5	1.500	923
1200	70.330.1200.41	1200X29,4 SDR41 ISO S-20	214.000	1.200	29,4	1.800	1.007
1400	70.330.1400.41	1400X34,3 SDR41 ISO S-20	290.000	1.400	34,3	1.705	1.006
1600	70.330.1600.41	1600X39,2 SDR41 ISO S-20	404.000	1.600	39,2	1.920	1.073
1800	70.330.1800.41	1800X44,0 SDR41 ISO S-20	543.000	1.800	44	2.160	1.144
2000	70.330.2000.41	2000X48,9 SDR41 ISO S-20	711.000	2.000	48,9	2.400	1.216



Boyut	Kod	Detay	Ağırlık	da(OD) mm	s mm	r mm	z mm
2250	70.330.2250.41	2250X55,0 SDR41 ISO S-20	965.000	2.250	55	2.700	1.305
560	70.330.0560.33	560X17,2 SDR33 ISO S-16	34.660	560	17,2	840	587
630	70.330.0630.33	630X19,3 SDR33 ISO S-16	45.000	630	19,3	945	616
710	70.330.0710.33	710X21,8 SDR33 ISO S-16	65.000	710	21,8	1.065	700
800	70.330.0800.33	800X24,5 SDR33 ISO S-16	87.000	800	24,5	1.200	738
900	70.330.0900.33	900X27,6 SDR33 ISO S-16	116.000	900	27,6	1.330	780
1000	70.330.1000.33	1000X30,6 SDR33 ISO S-16	169.000	1.000	30,6	1.500	923
1200	70.330.1200.33	1200X36,7 SDR33 ISO S-16	265.000	1.200	36,7	1.800	1.007
1600	70.330.1600.33	1600X49,0 SDR33 ISO S-16	501.000	1.600	49	1.920	1.073
1800	70.330.1800.33	1800X55,1 SDR33 ISO S-16	676.000	1.800	55,1	2.160	1.144
2000	70.330.2000.33	2000X61,2 SDR33 ISO S-16	885.000	2.000	61,2	2.400	1.216
2250	70.330.2250.33	2250X68,9 SDR33 ISO S-16	1,200.000	2.250	68,9	2.700	1.305
560	70.330.0560.26	560X21,4 SDR26 ISO S-12,5	42.300	560	21,4	840	587
630	70.330.0630.26	630X24,1 SDR26 ISO S-12,5	56.000	630	24,1	945	616
710	70.330.0710.26	710X27,2 SDR26 ISO S-12,5	80.000	710	27,2	1.065	700
800	70.330.0800.26	800X30,6 SDR26 ISO S-12,5	107.000	800	30,6	1.200	738
900	70.330.0900.26	900X34,4 SDR26 ISO S-12,5	143.000	900	34,4	1.330	780



Boyut	Kod	Detay	Ağırlık	da(OD) mm	s mm	r mm	z mm
1000	70.330.1000.26	1000X38,2 SDR26 ISO S-12,5	210.000	1.000	38,2	1.500	923
1200	70.330.1200.26	1200X45,8 SDR26 ISO S-12,5	328.000	1.200	45,9	1.800	1.007
1400	70.330.1400.26	1400X53,5 SDR26 ISO S-12,5	447.000	1.400	53,5	1.705	1.006
1600	70.330.1600.26	1600X61,2 SDR26 ISO S-12,5	621.000	1.600	61,2	1.920	1.073
1800	70.330.1800.26	1800X68,8 SDR26 ISO S-12,5	836.000	1.800	68,8	2.160	1.144
2000	70.330.2000.26	2000X76,4 SDR26 ISO S-12,5	1,095.000	2.000	76,4	2.400	1.216
2250	70.330.2250.26	2250X86,0 SDR26 ISO S-12,5	1,485.000	2.250	86	2.700	1.305
560	70.330.0560.17	560X33,2 SDR17 ISO S-8	64.000	560	33,2	840	587
630	70.330.0630.17	630X37,4 SDR17 ISO S-8	84.000	630	37,4	945	616
710	70.330.0710.17	710X42,1 SDR17 ISO S-8	122.000	710	42,1	1.065	700
800	70.330.0800.17	800X47,4 SDR17 ISO S-8	162.000	800	47,4	1.200	738
900	70.330.0900.17	900X53,3 SDR17 ISO S-8	216.000	900	53,3	1.350	780
1000	70.330.1000.17	1000X59,2 SDR17 ISO S-8	317.000	1.000	59,3	1.500	923
1200	70.330.1200.17	1200X71,1 SDR17 ISO S-8	496.000	1.200	71,1	1.800	1.007
1400	70.330.1400.17	1400X83,0 SDR17 ISO S-8	676.000	1.400	83	1.705	1.006
1600	70.330.1600.17	1600X94,8 SDR17 ISO S-8	939.000	1.600	94,8	1.920	1.073
1800	70.330.1800.17	1800X106,6 SDR17 ISO S-8	1,265.000	1.800	106,6	2.160	1.144
2000	70.330.2000.17	2000X118,5 SDR17 ISO S-8	1,658.000	2.000	118,5	2.400	1.216
2250	70.330.2250.17	2250X133,3 SDR17 ISO S-8	2,248.000	2.250	133,3	2.700	1.305



Boyut	Kod	Detay	Ağırlık	da(OD) mm	s mm	r mm	z mm
560	70.330.0560.11	560X50,8 SDR11 ISO S-5	94.300	560	50,8	840	587
630	70.330.0630.11	630X57,2 SDR11 ISO S-5	124.000	630	57,2	945	616
710	70.330.0710.11	710X64,5 SDR11 ISO S-5	179.000	710	64,5	1.065	700
800	70.330.0800.11	800x72,6 SDR11 ISO S-5	239.000	800	72,6	1.200	738
900	70.330.0900.11	900X81,7 SDR11 ISO S-5	320.000	900	81,7	1.350	780
1000	70.330.1000.11	1000X90,8 SDR11 ISO S-5	468.000	1.000	90,8	1.500	923
1200	70.330.1200.11	1200X108,9 SDR11 ISO S-5	733.000	1.200	108,9	1.800	1.007
1400	70.330.1400.11	1400X127,0 SDR11 ISO S-5	998.000	1.400	127	1.705	1.006
1600	70.330.1600.11	1600X145,2 SDR11 ISO S-5	1,387.000	1.600	145,2	1.920	1.073