



45° Bükme Her iki taraf 300 mm uzatılmış  
Enjeksiyon kalıplama+kaynak Alın + E-  
füzyon kaynağı PE 100-RC siyah

Boyut	Kod	Detay	Ağırlık	da(OD) mm	s mm	L mm	L1 mm	L2 mm
400	70.001.2400.26	400X15,3 SDR26 ISO S-12,5	23.000	400	15,3	300	469	424
355	70.001.2355.17	355X21,1 SDR17 ISO S-8	21.100	355	21,1	300	464	424
400	70.001.2400.17	400X23,7 SDR17 ISO S-8	25.800	400	23,7	300	469	424
450	70.001.2450.17	450X26,7 SDR17 ISO S-8	36.100	450	26,7	300	511	466
500	70.001.2500.17	500X29,7 SDR17 ISO S-8	44.100	500	29,7	300	511	466
355	70.001.2355.11	355X32,2 SDR11 ISO S-5	29.800	355	32,2	300	464	424
400	70.001.2400.11	400X36,3 SDR11 ISO S-5	37.900	400	36,3	300	469	424
450	70.001.2450.11	450X40,9 SDR11 ISO S-5	53.100	450	40,9	300	511	466
500	70.001.2500.11	500X45,4 SDR11 ISO S-5	66.700	500	45,4	300	511	466