



45° T uzun spigot W/P-TW enjeksiyon kalıplı Alın + E-füzyon kaynağı PE 100-RC siyah

Boyut	Kod	Detay	Ağırlık	da(OD) mm	s mm	z mm	L mm	L1 mm	L3 mm
63	70.036.0063.17	63X3,8 SDR17 PN10	0.388	63	3,8	170	262	93	64
75	70.036.0075.17	75X4,5 SDR17 PN10	0.620	75	4,5	191	294	103	71
90	70.036.0090.17	90X5,4 SDR17 PN10	1.080	90	5,4	230	354	122	82
110	70.036.0110.17	110X6,6 SDR17 PN10	1.590	110	6,6	248	380	131	84
125	70.036.0125.17	125X7,4 SDR17 PN10	2.667	125	7,4	297,5	440	140	93
140	70.036.0140.17	140X8,3 SDR17 PN10	3.300	140	8,3	315,5	460	150	94
160	70.036.0160.17	160X9,5 SDR17 PN10	4.820	160	9,5	360	521	166	98
180	70.036.0180.17	180X10,7 SDR17 PN10	6.440	180	10,7	380	557	179	105
200	70.036.0200.17	200X11,9 SDR17 PN10	8.430	200	11,9	407	598	191	113
225	70.036.0225.17	225X13,4 SDR17 PN10	12.100	225	13,4	464	670	206	120
32	70.036.0032.11	32X3,0 SDR11 PN16	0.120	32	3	131	195	65	45



Boyut	Kod	Detay	Ağırlık	da(OD) mm	s mm	z mm	L mm	L1 mm	L3 mm
40	70.036.0040.11	40X3,7 SDR11 PN16	0.174	40	3,7	137	208	72	50
50	70.036.0050.11	50X4,6 SDR11 PN16	0.276	50	4,6	144	224	81	56
63	70.036.0063.11	63X5,8 SDR11 PN16	0.507	63	5,8	173	262	93	64
75	70.036.0075.11	75X6,8 SDR11 PN16	0.781	75	6,8	191	294	103	71
90	70.036.0090.11	90X8,2 SDR11 PN16	1.380	90	8,2	230	351	122	82
110	70.036.0110.11	110X10,0 SDR11 PN16	2.110	110	10	253	382	131	84
125	70.036.0125.11	125X11,4 SDR11 PN16	3.282	125	11,4	299	431	140	92
140	70.036.0140.11	140X12,7 SDR11 PN16	4.280	140	12,7	315,5	460	150	94
160	70.036.0160.11	160X14,6 SDR11 PN16	6.350	160	14,6	362	521	166	100
180	70.036.0180.11	180X16,4 SDR11 PN16	8.600	180	16,4	385	562	179	107
200	70.036.0200.11	200X18,2 SDR11 PN16	11.240	200	18,2	416	605	191	114
225	70.036.0225.11	225X20,5 SDR11 PN16	16.060	225	20,5	474	673	206	122