



90° Dirsek Kısa Bağlantı Parçası  
Enjeksiyon Kalıplama Alın Kaynak PE 100-  
RC Siyah

Boyut	Kod	Detay	Ağırlık	da(OD) mm	s mm	r mm	z mm
63	70.001.0063.11	63X5,8 SDR11 ISO S-5	0.110	63	5,8	63	70
75	70.001.0075.11	75X6,8 SDR11 ISO S-5	0.213	75	6,8	75	85
90	70.001.0090.11	90X8,2 SDR11 ISO S-5	0.373	90	8,2	90	100
110	70.001.0110.11	110X10,0 SDR11 ISO S-5	0.625	110	10	110	124
125	70.001.0125.11	125X11,4 SDR11 ISO S-5	0.910	125	11,4	125	140
140	70.001.0140.11	140X12,7 SDR11 ISO S-5	1.240	140	12,7	140	150
160	70.001.0160.11	160X14,6 SDR11 ISO S-5	1.950	160	14,6	155	180
180	70.001.0180.11	180X16,4 SDR11 ISO S-5	2.730	180	16,4	180	200
200	70.001.0200.11	200X18,2 SDR11 ISO S-5	3.680	200	18,2	200	220
225	70.001.0225.11	225X20,5 SDR11 ISO S-5	5.070	225	20,5	225	243
250	70.001.0250.11	250X22,7 SDR11 ISO S-5	8.020	250	22,7	265	290
280	70.001.0280.11	280X25,4 SDR11 ISO S-5	9.750	280	25,4	265	290
315	70.001.0315.11	315X28,6 SDR11 ISO S-5	14.360	315	28,6	300	340
355	70.001.0355.11	355X32,2 SDR11 ISO S-5	18.460	355	32,2	300	340
400	70.001.0400.11	400X36,3 SDR11 ISO S-5	23.850	400	36,3	300	345
450	70.001.0450.11	450X40,9 SDR11 ISO S-5	38.800	450	40,9	400	445
500	70.001.0500.11	500X45,4 SDR11 ISO S-5	50.220	500	45,4	400	445