



İnegal Te Kısa musluk Enjeksiyon  
kalıplama Alttan kaynak PE 100-RC siyah

Boyut	Kod	Detay	Ağırlık	da(OD) mm	da1(OD1) mm	s mm	s1 mm	z mm	L mm	L1 mm	L2 mm
125/63	70.016.1263.11	125/63 SDR11 ISO S-5	1.420	125	63	11,4	5,8	112	275	75	31
140/63	70.016.1463.11	140/63 SDR11 ISO S-5	1.880	140	63	12,7	5,8	120	302	87	32
140/75	70.016.1475.11	140/75 SDR11 ISO S-5	1.850	140	75	12,7	6,8	130	302	87	35
140/90	70.016.1490.11	140/90 SDR11 ISO S-5	1.967	140	90	12,7	8,2	130	305	88	42
140/110	70.016.1411.11	140/110 SDR11 ISO S-5	2.280	140	110	12,7	10	141	305	54	47
160/125	70.016.1612.11	160/125 SDR11 ISO S-5	2.820	160	125	14,6	11,4	150	325	62	52
180/63	70.016.1863.11	180/63 SDR11 ISO S-5	3.160	180	63	16,4	5,8	139	358	132	32
180/75	70.016.1875.11	180/75 SDR11 ISO S-5	3.180	180	75	16,4	6,8	144	362	119	31
180/125	70.016.1812.11	180/125 SDR11 ISO S-5	3.360	180	125	16,4	11,4	166	362	100	52



Boyut	Kod	Detay	Ağırlık	da(OD) mm	da1(OD1) mm	s mm	s1 mm	z mm	L mm	L1 mm	L2 mm
225/125	70.016.2212.11	225/125 SDR11 ISO S-5	6.400	225	125	20,5	11,4	178	456	143	45