



İnegal Te kısa ağızlı işlenmiş alın kaynaklı
PE 100-RC siyah

Boyut	Kod	Detay	Ağırlık	da(OD) mm	da1(OD1) mm	s mm	s1 mm	z mm	L mm	L3 mm	d1 mm
560/160	70.307.5616.11	560/160 SDR11 ISO S-5	58.800	560	160	50,8	14,6	405	510	150	631
560/225	70.307.5622.11	560/225 SDR11 ISO S-5	46.000	560	225	50,8	20,5	450	570	150	625
560/315	70.307.5631.11	560/315 SDR11 ISO S-5	90.000	560	315	50,8	28,6	510	515	75	700
560/355	70.307.5635.11	560/355 SDR11 ISO S-5	83.600	560	355	50,8	32,2	455	555	75	710
630/250	70.307.6325.11	630/250 SDR11 ISO S-5	114.000	630	250	57,2	22,7	545	610	150	699
630/280	70.307.6328.11	630/280 SDR11 ISO S-5	71.900	630	280	57,2	25,4	550	640	150	720
630/315	70.307.6331.11	630/315 SDR11 ISO S-5	150.000	630	315	57,2	28,6	540	665	150	750
630/355	70.307.6335.11	630/355 SDR11 ISO S-5	119.000	630	355	57,2	32,2	550	710	150	790
630/400	70.307.6340.11	630/400 SDR11 ISO S-5	128.500	630	400	57,2	36,3	550	760	150	802



Boyut	Kod	Detay	Ağırlık	da(OD) mm	da1(OD1) mm	s mm	s1 mm	z mm	L mm	L3 mm	d1 mm
630/500	70.307.6350.11	630/500 SDR11 ISO S-5	187.000	630	500	57,2	45,4	650	860	150	870