



Yüksek basınç flanşı DIN PN20
sızdırmazlık halkası + destek halkası dahil
ve merkezleme halkası delikli PN25 Alın
kaynaklı PE 100-RC siyah

Boyut	Kod	Detay	Ağırlık	da(OD) mm	s mm	L mm	L3 mm	d mm	d2 mm	d4 mm	h mm
63	70.292.0063.09	63X7,1 SDR9 ISO S-4	2.820	63	7,1	100	63	165	18	102	17
75	70.292.0075.09	75X8,4 SDR9 ISO S-4	3.910	75	8,4	105	63	185	18	122	20
90	70.292.0090.09	90X10,1 SDR9 ISO S-4	4.810	90	10,1	105	60	200	18	137	21
110	70.292.0110.09	110X12,3 SDR9 ISO S-4	6.750	110	12,3	110	62	235	22	163	22
125	70.292.0125.09	125X14,0 SDR9 ISO S-4	6.475	125	14	120	64	235	22	163	30
140	70.292.0140.09	140X15,7 SDR9 ISO S-4	9.100	140	15,7	120	62	270	26	189	30
160	70.292.0160.09	160X17,9 SDR9 ISO S-4	12.400	160	17,9	120	60	300	26	219	30
180	70.292.0180.09	180X20,1 SDR9 ISO S-4	10.840	180	20,1	120	60	300	26	219	30



Boyut	Kod	Detay	Ağırlık	da(OD) mm	s mm	L mm	L3 mm	d mm	d2 mm	d4 mm	h mm
200	70.292.0200.09	200X22,4 SDR9 ISO S-4	18.800	200	22,4	135	64	360	26	279	39
225	70.292.0225.09	225X25,2 SDR9 ISO S-4	16.520	225	25,2	135	64	360	26	279	39
250	70.292.0250.09	250X27,9 SDR9 ISO S-4	28.500	250	27,9	145	60	425	30	335	50
280	70.292.0280.09	280X31,3 SDR9 ISO S-4	24.000	280	31,3	145	60	425	30	335	50
315	70.292.0315.09	315X35,2 SDR9 ISO S-4	36.210	315	35,2	195	100	485	30	395	57
355	70.292.0355.09	355X39,7 SDR9 ISO S-4	53.380	355	39,7	205	100	555	33	452	63
400	70.292.0400.09	400X44,7 SDR9 ISO S-4	74.890	400	44,7	220	102	620	36	509	70
450	70.292.0450.09	450X50,3 SDR9 ISO S-4	134.120	450	50,3	245	104	730	36	619	83
500	70.292.0500.09	500X55,8 SDR9 ISO S-4	118.550	500	55,8	245	101	730	36	619	86
560	70.292.0560.09	560X62,5 SDR9 ISO S-4	191.000	560	62,5	260	102	845	39	726	90
630	70.292.0630.09	630X70 SDR9 ISO S-4	157.000	630	70,3	258	100	845	39	726	90