



Redüksiyon konsantrik kısa spigot
işlenmiş Alın kaynaklı PE 100-RC siyah

Boyut	Kod	Detay	Ağırlık	da(OD) mm	da1(OD1) mm	s mm	s1 mm	L mm	L1 mm	L2 mm
75/63	70.317.7563.09	75/63 SDR9 ISO S-4	0.120	75	63	8,4	7,1	65	18	40
90/63	70.317.9063.09	90/63 SDR9 ISO S-4	0.160	90	63	10,1	7,1	75	21	40
90/75	70.317.9075.09	90/75 SDR9 ISO S-4	0.170	90	75	10,1	8,4	70	20	40
110/75	70.317.1175.09	110/75 SDR9 ISO S-4	0.290	110	75	12,3	8,4	80	24	40
125/75	70.317.1275.09	125/75 SDR9 ISO S-4	0.540	125	75	14	8,4	85	25	40
140/75	70.317.1475.09	140/75 SDR9 ISO S-4	0.610	140	75	15,7	8,4	95	30	40
140/90	70.317.1490.09	140/90 SDR9 ISO S-4	0.630	140	90	15,7	10,1	90	30	40
140/110	70.317.1411.09	140/110 SDR9 ISO S-4	0.590	140	110	15,7	12,3	115	40	30



Boyut	Kod	Detay	Ağırlık	da(OD) mm	da1(OD1) mm	s mm	s1 mm	L mm	L1 mm	L2 mm
140/125	70.317.1412.09	140/125 SDR9 ISO S-4	0.570	140	125	15,7	14	115	40	30
160/140	70.317.1614.09	160/140 SDR9 ISO S-4	0.870	160	140	17,9	15,7	125	40	30
180/90	70.317.1890.09	180/90 SDR9 ISO S-4	1.350	180	90	20,1	10,1	140	45	35
180/110	70.317.1811.09	180/110 SDR9 ISO S-4	1.400	180	110	20,1	12,3	135	45	35
180/125	70.317.1812.09	180/125 SDR9 ISO S-4	1.050	180	125	20,1	14	130	45	35
180/140	70.317.1814.09	180/140 SDR9 ISO S-4	1.380	180	140	20,1	15,7	130	45	35
180/160	70.317.1816.09	180/160 SDR9 ISO S-4	1.320	180	160	20,1	17,9	125	45	35
200/140	70.317.2014.09	200/140 SDR9 ISO S-4	1.440	200	140	22,4	15,7	145	50	40
200/180	70.317.2018.09	200/180 SDR9 ISO S-4	1.860	200	180	22,4	20,1	140	50	40
225/140	70.317.2214.09	225/140 SDR9 ISO S-4	2.150	225	140	25,2	15,7	110	40	40
225/180	70.317.2218.09	225/180 SDR9 ISO S-4	3.100	225	180	25,2	20,1	145	55	40
225/200	70.317.2220.09	225/200 SDR9 ISO S-4	1.867	225	200	25,2	22,4	90	37	40



Boyut	Kod	Detay	Ağırlık	da(OD) mm	da1(OD1) mm	s mm	s1 mm	L mm	L1 mm	L2 mm
250/180	70.317.2518.09	250/180 SDR9 ISO S-4	5.000	250	180	27,9	20,1	110	44	40
250/200	70.317.2520.09	250/200 SDR9 ISO S-4	3.600	250	200	27,9	22,4	100	40	40
280/160	70.317.2816.09	280/160 SDR9 ISO S-4	3.500	280	160	31,3	17,9	125	45	40
280/180	70.317.2818.09	280/180 SDR9 ISO S-4	7.000	280	180	31,3	20,1	120	45	40
280/200	70.317.2820.09	280/200 SDR9 ISO S-4	3.800	280	200	31,3	22,4	115	46	40
280/225	70.317.2822.09	280/225 SDR9 ISO S-4	4.600	280	225	31,3	25,5	105	43	40
280/250	70.317.2825.09	280/250 SDR9 ISO S-4	4.300	280	250	31,3	27,9	100	46	40
315/160	70.317.3116.09	315/160 SDR9 ISO S-4	4.980	315	160	35,2	17,9	140	49	40
315/180	70.317.3118.09	315/180 SDR9 ISO S-4	4.600	315	180	35,2	20,1	135	50	40
315/200	70.317.3120.09	315/200 SDR9 ISO S-4	5.225	315	200	35,2	22,4	125	46	40
315/225	70.317.3122.09	315/225 SDR9 ISO S-4	5.200	315	225	35,2	25,5	120	48	40
315/250	70.317.3125.09	315/250 SDR9 ISO S-4	5.800	315	250	35,2	27,9	115	50	40



Boyut	Kod	Detay	Ağırlık	da(OD) mm	da1(OD1) mm	s mm	s1 mm	L mm	L1 mm	L2 mm
315/280	70.317.3128.09	315/280 SDR9 ISO S-4	6.000	315	280	35,2	31,3	105	49	40
355/180	70.317.3518.09	355/180 SDR9 ISO S-4	8.000	355	180	39,7	20,1	155	53	40
355/200	70.317.3520.09	355/200 SDR9 ISO S-4	9.000	355	200	39,7	22,4	150	54	40
355/225	70.317.3522.09	355/225 SDR9 ISO S-4	8.600	355	225	39,7	25,5	140	51	40
355/250	70.317.3525.09	355/250 SDR9 ISO S-4	8.800	355	250	39,7	27,9	130	48	40
355/280	70.317.3528.09	355/280 SDR9 ISO S-4	9.200	355	280	39,7	31,3	125	52	40
355/315	70.317.3531.09	355/315 SDR9 ISO S-4	7.000	355	315	39,7	35,2	115	52	40
400/180	70.317.4018.09	400/180 SDR9 ISO S-4	9.600	400	180	44,7	20,1	170	55	40
400/225	70.317.4022.09	400/225 SDR9 ISO S-4	8.800	400	225	44,7	25,5	160	58	40
400/250	70.317.4025.09	400/250 SDR9 ISO S-4	10.400	400	250	44,7	27,9	150	55	40
400/280	70.317.4028.09	400/280 SDR9 ISO S-4	10.800	400	280	44,7	31,3	140	54	40
400/315	70.317.4031.09	400/315 SDR9 ISO S-4	9.000	400	315	44,7	35,2	130	54	40



Boyut	Kod	Detay	Ağırlık	da(OD) mm	da1(OD1) mm	s mm	s1 mm	L mm	L1 mm	L2 mm
400/355	70.317.4035.09	400/355 SDR9 ISO S-4	8.800	400	355	44,7	39,7	120	55	40
450/225	70.317.4522.09	450/225 SDR9 ISO S-4	14.000	450	225	50,3	25,5	180	64	40
450/250	70.317.4525.09	450/250 SDR9 ISO S-4	7.070	450	250	50,3	27,9	170	61	40
450/280	70.317.4528.09	450/280 SDR9 ISO S-4	14.800	450	280	50,3	31,3	160	59	40
450/315	70.317.4531.09	450/315 SDR9 ISO S-4	14.200	450	315	50,3	35,2	150	59	40
450/355	70.317.4535.09	450/355 SDR9 ISO S-4	16.000	450	355	50,3	39,7	140	61	40
450/400	70.317.4540.09	450/400 SDR9 ISO S-4	16.500	450	400	50,3	44,7	125	59	40
500/315	70.317.5031.09	500/315 SDR9 ISO S-4	17.400	500	315	55,8	35,2	175	70	40
500/355	70.317.5035.09	500/355 SDR9 ISO S-4	17.400	500	355	55,8	39,7	165	72	40
500/400	70.317.5040.09	500/400 SDR9 ISO S-4	18.000	500	400	55,8	44,7	150	70	40
500/450	70.317.5045.09	500/450 SDR9 ISO S-4	21.000	500	450	55,8	50,3	250	65	75
560/315	70.317.5631.09	560/315 SDR9 ISO S-4	21.000	560	315	62,5	36,2	250	65	75



Boyut	Kod	Detay	Ağırlık	da(OD) mm	da1(OD1) mm	s mm	s1 mm	L mm	L1 mm	L2 mm
560/355	70.317.5635.09	560/355 SDR9 ISO S-4	23.000	560	355	62,5	39,7	250	65	75
560/400	70.317.5640.09	560/400 SDR9 ISO S-4	25.000	560	400	62,5	44,7	250	65	75
560/450	70.317.5645.09	560/450 SDR9 ISO S-4	27.000	560	450	62,5	50,3	250	65	75
560/500	70.317.5650.09	560/500 SDR9 ISO S-4	29.000	560	500	62,5	55,8	250	65	90
630/355	70.317.6335.09	630/355 SDR9 ISO S-4	30.000	630	355	70,3	39,7	250	65	75
630/400	70.317.6340.09	630/400 SDR9 ISO S-4	32.000	630	400	70,3	44,7	250	65	75
630/450	70.317.6345.09	630/450 SDR9 ISO S-4	34.000	630	450	70,3	50,3	250	65	75
630/500	70.317.6350.09	630/500 SDR9 ISO S-4	36.000	630	500	70,3	55,8	250	65	90
630/560	70.317.6356.09	630/560 SDR9 ISO S-4	38.500	630	560	70,3	62,5	250	65	90