



45° Dirsek 4 segment Tam basınç dayanımlı Bölmeli Alın + E-füzyon kaynağı PE 100-RC siyah

| Boyut | Kod | Detay | Ağırlık | da(OD) mm | s mm | r mm | z mm |
|-------|----------------|-----------------------|---------|--------------|------|-------|------|
| 140 | 70.327.0140.09 | 140x15,7 SDR9 ISO S-4 | 3.100 | 140 | 15,7 | 450 | 239 |
| 160 | 70.327.0160.09 | 160x17,9 SDR9 ISO S-4 | 4.550 | 160 | 17,9 | 460 | 290 |
| 180 | 70.327.0180.09 | 180x20,1 SDR9 ISO S-4 | 6.400 | 180 | 20,1 | 470 | 320 |
| 250 | 70.327.0250.09 | 250x27,9 SDR9 ISO S-4 | 15.820 | 250 | 27,9 | 581 | 356 |
| 280 | 70.327.0280.09 | 280x31,3 SDR9 ISO S-4 | 20.180 | 280 | 31,3 | 596 | 362 |
| 315 | 70.327.0315.09 | 315x35,2 SDR9 ISO S-4 | 23.000 | 315 | 35,2 | 613 | 369 |
| 355 | 70.327.0355.09 | 355x39,7 SDR9 ISO S-4 | 53.700 | 355 | 39,7 | 1.127 | 642 |
| 400 | 70.327.0400.09 | 400x44,7 SDR9 ISO S-4 | 69.000 | 400 | 44,7 | 1.149 | 651 |
| 450 | 70.327.0450.09 | 450x50,3 SDR9 ISO S-4 | 88.640 | 450 | 50,3 | 1.174 | 661 |
| 500 | 70.327.0500.09 | 500x55,8 SDR9 ISO S-4 | 110.700 | 500 | 55,8 | 1.199 | 672 |
| 560 | 70.327.0560.09 | 560x62,5 SDR9 ISO S-4 | 142.000 | 560 | 62,5 | 1.343 | 766 |
| 630 | 70.327.0630.09 | 630x70 SDR9 ISO S-4 | 182.000 | 630 | 70,3 | 1.378 | 781 |