



45° Dirsek Uzun musluk Enjeksiyon
kalıplama Alt kaynak + IR kaynak PP Saf
gri

Boyut	Kod	Detay	Ağırlık	da(OD) mm	s mm	z mm	L3 mm
20	72.060.0020.11	20X1,9 SDR11 ISO S-5	0.013	20	1,9	44	42
25	72.060.0025.11	25X2,3 SDR11 ISO S-5	0.019	25	2,3	48	42
32	72.060.0032.11	32X2,9 SDR11 ISO S-5	0.033	32	2,9	57	49
40	72.060.0040.11	40X3,7 SDR11 ISO S-5	0.052	40	3,7	63	53
50	72.060.0050.11	50X4,6 SDR11 ISO S-5	0.090	50	4,6	70	57
63	72.060.0063.11	63X5,8 SDR11 ISO S-5	0.168	63	5,8	80	67
75	72.060.0075.11	75X6,8 SDR11 ISO S-5	0.279	75	6,8	101	72,5
90	72.060.0090.11	90X8,2 SDR11 ISO S-5	0.450	90	8,2	110	81,5
110	72.060.0110.11	110X10,0 SDR11 ISO S-5	0.740	110	10	120	85
125	72.060.0125.11	125X11,4 SDR11 ISO S-5	1.023	125	11,4	132,5	95
140	72.060.0140.11	140X12,7 SDR11 ISO S-5	1.375	140	12,7	142	100
160	72.060.0160.11	160X14,6 SDR11 ISO S-5	1.919	160	14,6	153	105
180	72.060.0180.11	180X16,4 SDR11 ISO S-5	2.547	180	16,4	158,5	112
200	72.060.0200.11	200X18,2 SDR11 ISO S-5	3.348	200	18,2	170,5	120,5
225	72.060.0225.11	225X20,5 SDR11 ISO S-5	4.590	225	20,5	186	127



Boyut	Kod	Detay	Ağırlık	da(OD) mm	s mm	z mm	L3 mm
250	72.060.0250.11	250X22,7 SDR11 ISO S-5	6.800	250	22,7	217	160
280	72.060.0280.11	280X25,4 SDR11 ISO S-5	9.179	280	25,4	235	173
315	72.060.0315.11	315X28,6 SDR11 ISO S-5	12.130	315	28,6	250	179